

# EPX+ Series

10 ~ 40kVA  
3:3 Phase PF: 0.9

## Applications:

For all kind of ADP Machines



## Features:

- Online Double-Conversion.
- DSP Technology Guarantees High Reliability.
- Isolation Transformer Compatible
- Control Designed to Withstand all kinds of Loads.
- Intelligent Battery Management to Prolong Battery Life Cycle.
- Redundant Fan Design and Independent Ventilation Enhances Durable Operation Under Harsh Environment.
- Adjustable Battery Numbers.
- Accept Dual-Mains Input.
- Parallel Operation with up to 6 Units (Option).
- Variety of Communication Options Available.
- 7" Inch Colour Touch Screen Display
- IGBT based charger for smart battery management & improve input power factor
- EPO & ECO Mode Operation



7" Touch Screen



MODEL	EPX+3310L32	EPX+3320L32	EPX+3330L32	EPX+3340L32
Capacity	10kVA	20kVA	30kVA	40kVA
<b>INPUT</b>				
Rated AC Voltage	380V / 400V / 415V AC (3Ph+N+PE)			
Voltage Range	290V ~ 480V AC			
Frequency Range	50 / 60 Hz ± 10% Auto Sensing			
Power Factor	≥ 0.95 (With Filter)			
Walk-in Time	5 ~ 300 Sec. (Configurable)			
<b>BYPASS</b>				
Rated Voltage	380V / 400V / 415V AC (3Ph+N+PE)			
Voltage Range	+ 20%, -30% (Configurable)			
Frequency Range	50 / 60 Hz ± 10% (Configurable)			
<b>BATTERY</b>				
Battery Voltage	384V DC Standard (360 ~ 408 Configurable)			
Ripple	≤ 1%			
Charging Current Max. (A)	0.10C to 0.25C upto 100~300Ah at 100% Load (Configurable)			
<b>OUTPUT</b>				
Rated Voltage	380V / 400V / 415V AC (3Ph+N)			
Frequency Range	Auto Sensing 50 / 60 Hz ± 1~10% Sync Mode (Configurable), 50/60 Hz ± 0.1 Hz Battery Mode			
Voltage Regulation	±1%			
Harmonic Distortion (THDv)	≤ 1% Linear Load, ≤ 5% Non-Linear Load			
Crest Factor / Transfer Time	3:1 / Zero			
Efficiency	Up to 95% Dual Conversion Mode, 99% ECO Mode			
Overload	≤ 110% for 60 Min, ≤ 125% for 10 Min, ≤ 150% for 1 Min, ≥ 150% for 300 ms			
<b>SYSTEM FEATURES</b>				
Parallel	Up to 6 Units (Optional)			
Display	Touch Screen & LED Mimic Diagram			
IP Rating	IP20			
Alarm / Protection	Short Circuit, Input Under/Over Voltage, Over Temperature, Over Current,			
Audible Alarms	Alarm for batt. Low, DC High, Inverter Under/Over Voltage, Overload, Short Circuit, Fan Failure & UPS Fault			
LED Indicatos	Bypass, Mains, Battery and Fault			
LCD Information	Input Voltage & Freq.; Output Voltage, Current, kVA, kW, Total Power, PF, Load % Per Phase, Load % Total & Freq.; Bypass Voltage & Freq.; Inverter Voltage & Freq.; Battery Voltage, DC Bus Voltage, Charging Current, Discharging Current, Temperature.			
<b>ENVIRONMENTAL</b>				
Temperature	Operating: 0~50°C*, Storage: -10°C ~ 55°C			
Humidity / Altitude	0~95% RH Non-condensing / <1500 M			
Noise	<65dBA			
<b>STANDARDS</b>				
Quality	ISO 9001, ISO 14001, ISO 27001, ISO45001, ISO 50001, RoHS			
Safety	IEC/EN62040-1			
EMC / Performance	IEC/EN62040-2; IEC/EN62040-3, Complying to CE			
<b>PHYSICAL</b>				
Dimensions WxDxH (mm)	350x650x1050		430x830x1100	
Weight (Kg)	155	190	242	315
<b>COMMUNICATION INTERFACE</b>				
Standard	RS-232			
Optional	SNMP / ModBus / Dry Contact / USB / RS-485			
Monitoring Software	NetAgent / Muser4000			

\*Conditions apply  
Specifications are subject to change without prior notice.

## Best Power Equipments India Pvt. Ltd.

Corporate Office: G-240, Sector-63, Distt. Gautam Buddh Nagar, Noida-201307 UP  
Registered Office: 812A, Shakuntala Building, 59, Nehru Place, New Delhi-110019  
PH: +91 120 4637000-0029 | Mobile: +91 9311995859 | Email: crm@bpee.co.in  
support@bpeindia.com | Toll Free: 1800 103 1247 | Website: www.bpee.com

POWER IS ON

