

GTP Series

60/80/100kVA
3:3 Phase

Applications:

For all kind of ADP Machines



Features:

- ◆ True Online Double Conversion Topology
- ◆ 3-Level IGBT Based Rectifier & Inverter
- ◆ Wide Input Voltage Range
- ◆ High Input Power Factor : ≥ 0.99
- ◆ Wide Input Frequency Range : 50/60Hz $\pm 20\%$
- ◆ Inbuilt Phase Sequence Correction
- ◆ Parallel upto 4 units
- ◆ Static Bypass and Cold Start
- ◆ High Output Power Factor : 1.0 (kVA=kW)
- ◆ Low Harmonic Distortion : $< 2\%$
- ◆ Configurable Batteries : 30~50 Nos.
- ◆ Transformer Compatible
- ◆ IOT Compatible



Control Panel



MODEL		GTP3360L32	GTP3380L32	GTP33100L32
Capacity (kVA)		60	80	100
INPUT				
Nominal Voltage		380V / 400V / 415V AC (3Ph+N+PE)		
Voltage Range		+25% – 35%		
Frequency Range		50 / 60 Hz ± 20% Auto Sensing		
Power Factor		≥ 0.99		
Harmonic Distortion (THDi)		≤3%		
Bypass Range	Voltage	35% (Optional -20%, -30%)		
	Frequency	± 10% (Configurable)		
Generator Input		Support		
OUTPUT				
Output Voltage		380V / 400V / 415V AC (3Ph+N+PE)		
Voltage Regulation		± 1%		
Power Factor		1.0 Standard		
Frequency		Auto Sensing 50 / 60 Hz ± 1~10% Sync Mode (Configurable), 50/60 Hz ± 0.1 Hz Battery Mode		
Crest Factor		3:1		
Harmonic Distortion (THDv)		≤ 2%		
Overload		≤125% for 10 Min, ≤ 150% for 1 Min, ≥ 150% for 200 ms		
Efficiency		96.5% Dual Conversion Mode, 99% ECO Mode		
BATTERY				
Battery Voltage		360 - 600V DC		
SYSTEM FEATURES				
Transfer Time		Zero		
Self-Diagnostics / EPO		Upon Power On and Software Control / Inbuilt		
IP Protection		IP 20		
Alarm / Protection		Line Failure, Battery Low, Overload, System Fault and Short Circuit		
Display	LED	Line Mode, Bypass Mode, Battery Low, Overload and UPS Fault Codes		
	LCD	Input Voltage, Input Frequency, Output Voltage, Output Frequency, Load %, Battery Voltage & Temperature, Output W/VA		
Parallel		Inbuilt		
ENVIRONMENT				
Temperature		Operating: 0~50°C*, Storage: -10°C ~ 55°C		
Humidity / Altitude		0~95% RH Non-condensing / <1500 M		
Noise		<60dBA		
STANDARDS				
Quality		ISO 9001, ISO 14001, ISO 27001, ISO 45001, ISO 50001, RoHS		
Safety		IEC/EN62040-1		
EMC / Performance		IEC/EN62040-2; IEC/EN62040-3, Complying to CE		
PHYSICAL				
Dimension WxDxH (mm)		250x580x655	850x442x1200	
Net Weight (Kg)		80	135	170
COMMUNICATION INTERFACE				
Standard		RS-232		
Optional		SNMP / ModBus / Dry Contact / USB / RS-485		
Monitoring Software		NetAgent Utility v5.8 / View Power / UPSilon 2000 / Muser 4000		

*Conditions apply.

Specifications are subject to change without prior notice.

Best Power Equipments India Private Limited

Corporate Office: G-240, Sector-63, Distt. Gautam Buddh Nagar, Noida-201307 UP
 Registered Office: 812A, Shakuntala Building, 59, Nehru Place, New Delhi-110019
 PH: +91 120 4637000-0029 | Mobile: +91 9311995859 | Email: crm@bpee.co.in
 support@bpeindia.com | Toll Free: 1800 103 1247 | Website: www.bpee.com

POWER IS ON

