

MF Series

6kVA (1:1)

PF: 1.0

Applications:

For all kind of ADP Machines



LCD Panel



Features:

- True Online Double Conversion Topology
- DSP Controlled Design
- Pure Sine wave output waveform
- IGBT based both Rectifier & Inverter
- Wide Input Voltage Range (110V -300V AC)
- High Input Power Factor (≥ 0.99)
- Input Current Harmonic $\leq 3\%$
- Wide Input Frequency Range
- High Output Power Factor (Unity, kVA=kW)
- Optimization Battery Group (192V/216V/240V DC)
- CVCF Based Charging for long battery life
- ECO mode for energy saving
- Self-Testing while UPS Startup
- Common Battery Bank Operation
- Static Bypass and Integrated Maintenance Bypass
- Auto Restart and Cold start function
- Optional Parallel Compatibility up to 4 units
- Inbuilt Surge Protection
- Generator Compatibility



MODEL		MF1106B16	MF1106L16
Capacity (kVA/kW)		6 kVA/kW	
Type		Internal Battery	External Battery
INPUT			
Nominal Voltage		220V/230V/240V AC (P+N+PE)	
Operating Voltage Range		110V~300V AC (Load Dependant)	
Operating Frequency Range		50/60 Hz ± 10% (Auto Sensing)	
Power Factor		≥ 0.99	
Bypass	Voltage	- 40% ~ +15% (Configurable)	
	Frequency	± 5% (Configurable)	
ECO Mode Range		Same as the Bypass (Configurable)	
Generator Input		Compatible	
OUTPUT			
Rated Voltage (Configurable)		220V/230V/240V AC (P+N+PE)	
Power Factor		1.0	
Voltage Regulation		±1%	
Frequency		Auto Sensing 50/60 Hz ± 1~10% Sync Mode (Configurable), 50/60 Hz ± 0.1% Battery Mode	
Crest Factor		3:1	
Overload		≤105% for Continuos, ≤ 125% for 10 Min, ≤ 150% for 60 Sec, ≥ 150% for 200ms	
Harmonic Distortion (THDv)		≤ 1%	
Efficiency		94.0% Dual Conversion Mode, 99.0% ECO Mode	
BATTERY			
Battery Type		SMF VRLA 12V/9Ah	SMF VRLA / Lithium-ion
Battery Voltage		Inbuilt 16 Nos. of 12V/9Ah	192V/216V/240V DC (Configurable), 3-wire
Typical Recharge Time		4-5 Hours to 90% of full Capacity	
Charge Current		1A~6.5A configurable (standard) ; 10A (optional)	
SYSTEM FEATURES			
IP Protection		IP20	
Transfer Time		Zero	
EPO		Shutdown UPS Immediately	
Alarm / Protection		Short Circuit, Input Under/Over Voltage, Over Temperature, Output Over Load, DC Bus Under/Over Voltage, Battery low, Input Surge protection	
LED Indication		Line Mode, Battery Mode, ECO Mode, Bypass Mode, Battery Low, Overload & UPS Fault	
LCD		Input Voltage/Frequency, Output Voltage/Frequency, Load Current, Load Percentage, Battery Voltage, Charging/Discharging Current, Load/Battery Barograph, Temperature, Remaining Battery Backup Time, Load VA/W, Operating mode & Fault mode	
ENVIRONMENTAL			
Temperature		Operating: 0~50°C*, Storage: -15°C ~ 60°C	
Humidity / Altitude		0~95% RH Non-condersing / <1500 M	
Noise		<55dBA	
PHYSICAL			
Dimension WxDxH (mm)		190 x 480 x 750	190 x 480 x 350
Net Weight (Kg)		82	25
STANDARDS			
Quality		ISO 90001, ISO 14001, ISO 27001, ISO 45001, ISO 50001, BIS, RoHS, FCC	
Safety		IEC/EN62040-1; Conformity to IEC / EN	
EMC / Performance		IEC/EN62040-2; IEC/EN62040-3, Complying to CE	
COMMUNICATION INTERFACE			
Standard		RS-232/USB/EPO	
Optional		SNMP/ModBus/Dry Contact/IoT/Wi-fi & Bluetooth monitoring	
Monitoring Software		BPE Cyber / UPSilon 2000	

*Conditions apply.

Specifications are subject to change without prior notice.

Best Power Equipments India Pvt. Ltd.

Corporate Office: G-240, Sector-63, Distt. Gautam Buddh Nagar, Noida-201307 UP
 Registered Office: 812A, Shakuntala Building, 59, Nehru Place, New Delhi-110019
 PH: +91 120 4637000-0029 | Mobile: +91 9311995859 | Email: crm@bpe.co.in
 support@bpeindia.com | Toll Free: 1800 103 1247 | Website: www.bpee.com

POWER IS ON™

