



MODEL		GTM3360L32	GTM3390L32	GTM33120L32
Capacity (KVA)		60	90	120
<b>INPUT</b>				
Nominal Voltage		380V / 400V / 415V AC (3Ph+N+PE)		
Voltage Range		+25% – 35%		
Frequency Range		50 / 60 Hz ± 20% Auto Sensing		
Power Factor		≥ 0.99		
Harmonic Distortion (THDi)		2% (Non-Linear Load)		
Bypass Range	Voltage	35% (Optional -20%, -30%)		
	Frequency	± 10% (Configurable)		
Generator Input		Support		
<b>OUTPUT</b>				
Output Voltage		380V / 400V / 415V AC (3Ph+N+PE)		
Voltage Regulation		± 1%		
Power Factor		0.9 Standard / Unity Optional		
Frequency		Auto Sensing 50 / 60 Hz ± 1~10% Sync Mode (Configurable), 50/60 Hz ± 0.1 Hz Battery Mode		
Crest Factor		3:1		
Harmonic Distortion (THDv)		≤ 2% with Linear Load; ≤ 5% with Non-Linear Load		
Overload		≥ 125% for 10 Min, ≥ 150% for 1 Min, ≤ 150% for 200 ms		
Efficiency		Up to 95% Dual Conversion Mode, 99% ECO Mode		
<b>BATTERY</b>				
Battery Voltage		Standard Unit: ± 216V DC; Unit configurable Voltage: ± 192V / ± 204V / ± 216V / ± 228V / ± 240V DC		
<b>SYSTEM FEATURES</b>				
Transfer Time		Zero		
Self-Diagnostics / EPO		Upon Power On and Software Control / Inbuilt		
IP Protection		IP 20		
Alarm / Protection		Line Failure, Battery Low, Overload, System Fault and Short Circuit		
Display	LED	Line Mode, Bypass Mode, Battery Low, Overload and UPS Fault Codes		
	LCD	Input Voltage, Input Frequency, Output Voltage, Output Frequency, Load %, Battery Voltage & Temperature, Output W/VA		
Parallel		Inbuilt		
<b>ENVIRONMENT</b>				
Temperature		Operating: 0~45°C, Storage: -10°C ~ 55°C		
Humidity / Altitude		0~95% RH Non-condensing / <1500 M		
Noise		Low Audible Noise Level		
<b>STANDARDS</b>				
Quality		ISO 9001, ISO 14001, OHSAS 18001, ISO 27001, RoHS		
Safety		IEC/EN62040-1		
EMC / Performance		IEC/EN62040-2; IEC/EN62040-3, Complying to CE		
<b>PHYSICAL</b>				
Dimension WxDxH (mm)		600x780x1200		
Net Weight (Kg)		158	190	196
<b>COMMUNICATION INTERFACE</b>				
Standard		RS-232		
Optional		SNMP / ModBus / Dry Contact / USB / RS-485		
Monitoring Software		NetAgent Utility v5.8 / View Power / UPSilon 2000 / Muser 4000		

\*Specifications are subject to change without prior notice.