

# BC Series

## Features:

- Comprehensive UPS Management With Flexible Configuration
- Support Advance Encryption
- Centralized Authentication by Radius
- Event Notification via Email, SMS or Trap
- Support Environment Monitoring
- Multi-Language User Interface
- Real Time UPS Monitoring
- Schedule Periodic UPS Self-Test
- Record Event / Data Log
- Graceful Multi-Server Shutdown
- Battery Test Log



## Technical Specifications:

Product Model	BC802-R	BC803-M	BC803-S
CPU	ARM9 180MHz 32 Bit		
Port	1 Port		
Flash Memory	8 MB		
Web Multi-Language	Yes		
Power DC Input	5.3V~40V, 2W Max	5V~7V, 250mA Max	5V~15V, 250mA Max
Watch Dog	Yes		
LAN Interface	10M/100M UTP		
LAN Protocol	TCP/IP, HTTP, HTTPS, SSL, SSH, SMTP, SNMP, DHCP, Telnet, BOOTP, DNS, DDNS, PPPoE, RADIUS, IPv4, IPv6		
MIB	PPC MIB, RFC1628, SNMPv1, SNMPv2, SNMPv3		
Real Time Clock (RTC)	Yes		
Dimension (mm)	130 x 60		23 x 47

